

LTF

LTF "ACTIVE" SERIES WEIGHING KIT FOR LIFT TRUCK FORKS



Pair of forks with an integrated weighing system, for lift trucks, easy to use, sturdy, and reliable. Simple and easy to install, these replace the original forks and allow a clear visualisation of the loaded weight. Compatible with any lift truck having a DIN 15173 - FEM fork holder plate, of the IIA or IIIA class (IIB optional). Available in CE-M approved version.

The best solution
for advanced industrial
applications

MAIN FEATURES

- Weight indicator with waterproof keyboard, 5 keys, and protective case in extra thick steel, mounted on a fork and connected to the other fork by means of a cable.
- LCD backlit display with 6 digits 25mm high, easily visible in any lighting condition.
- Steel bearing I P 6 5 structure.
- Each fork weighs 75kg (LTF25) and 90kg (LTF50).
- Functions with 4 shear-beam IP68 load cells.
- Accuracy: +/- 0.2% of the capacity.
- Max. allowable overload: 200% of the nominal capacity.
- Max. horizontal inclination (flexibility): +/- 2° with the same accuracy characteristics.
- Power supply through rechargeable battery, the operating time is of about 40 hours of continuous use.
- Additional battery pack (optional) to use the system 24/7.
- Fitted with battery charger, compatible with LTFBK option.
- Auto switch-off function.
- Fitted with infrared remote control.
- Optional radio module for transmitting data to a PC or a remote repeater.

KEYBOARD FUNCTIONS



- Zeroing, semi automatic tare, presettable tare, function mode, stand-by
- NOTES: functions available also with infrared remote control.

SELECTABLE FUNCTIONS

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weighs totalisation
- Formulation
- +/- Check
- Percentage weighing
- Alibi memory, for weight approved transmission (optional)
- Counting
- Hold and Peak

VERSIONS

Available versions

| Code | Plate | Max (kg) | d (kg) | CE-M 3000e (kg) |
|---|-------|--------------------|------------|--------------------|
| LTF1125A-1 | FEM2A | 500 / 1000 / 2500 | 1 / 2 / 5 | |
| LTF1125AM-1 | FEM2A | 1000 / 2500 | | 2 / 5 |
|  LTF1150A-1 | FEM3A | 1000 / 2500 / 5000 | 2 / 5 / 10 | |
|  LTF1150AM-1 | FEM3A | 2500 / 5000 | | 5 / 10 |



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE