

DFWATEX

DFW "ATEX2GD": WEIGHT INDICATOR FOR ATEX 1 & 21 ZONES



Weight indicator for areas classified as hazardous with protection methods according to:

ATEX II 2(2)G Ex ib [ib Gb] IIC T4 Gb for gases,
ATEX II 2(2)D Ex tb [ib Db] IIIC T197°C IP65 Db for dust.

Ideal for creating weighing systems, batching, and automation systems. EC-Type-Examination certificate according to Annex III (ATEX directive). CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

P.R.S. TORFBUD

UL.KOPERNIKA 6 - 41500 - CHORZOW - POLAND
Tel. 0048-322413522 Fax. 0048-322413522
torfbud@wagielektroniczne.com.pl

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Waterproof 17-key numerical and functional keyboard.
- LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures, and with 6 LEDs for showing the active functions.
- Satined IP68 stainless steel case.
- Dimensions 264x174x115mm.
- Suitable for use on the table, or wall.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Digital calibration and set-up from keyboard; Instrument management & configuration from PC with DINITOOLS.
- Power supply through external module: with optional battery pack; or with optional power adapter connectable to mains at 230 Vac or at 24 Vdc.
- Connection with up to 4 load cells having 350 Ohm input resistance.

FUNCTIONS

- SCALE FUNCTIONS
 - Zeroing
 - Automatic Tare
 - Presetable Tare
 - ID1 and ID2 10-digit Codes
 - Print and data transmission commands
 - selectable function command
 - on/off switching.
- SELECTABLE FUNCTIONING MODES
 - High Resolution Weighing x 10
 - Net/Gross or lb/kg conversion
 - Accumulation
 - Formula weighing
 - +/- Checkweighing
 - Counting (Max. resolution of 1.500.000 divisions).
 - In/Out Truck weighing
 - Hold
 - Peer-to-peer (up to 4 remote connectable indicators).
 - Set Point Control (only in the DFWATEX2GDIO version combined with PW200XRDxxx and PW200IO options).
 - MODBUS serial protocol.

I/O SECTION (ONLY WITH THE DFWATEX2GDIO MODEL):

- Fiber optic bidirectional port for connection with printer, labeller, PC, or PLC in safe area.
- 4 logic inputs and 4 barriered digital outputs, connectable to other intrinsic safety devices in a hazardous area (only with the DFWATEX2GDIO version combined with PW200XRDxxx and PW200IO options).



DINI AR GEO
FRANCE sarl
 Nogent-sur-Marne

DINI AR GEO
GMBH
 Sinsheim - Germany

DINI AR GEO
UK Ltd
 Taunton - United Kingdom

DINI AR GEO WEIGHING
INSTRUMENTS Ltd
 Shanghai - China

DINI AR GEO
WEIGHBRIDGES
 Calto (RO) - Italy



HEAD OFFICE
 Via Della Fisica, 20
 41042 Spezzano di Fiorano Modena - Italy



P.R.S. TORFBUD

UL.KOPERNIKA 6 - 41500 - CHORZOW - POLAND

Tel. 0048-322413522 Fax. 0048-322413522

torfbud@wagielektroniczne.com.pl

SALES AND TECHNICAL ASSISTANCE SERVICE