

6116 PRO

Industrial touch screen PC "6116PRO" with integrated scale input



Industrial PC with AISI304 STAINLESS steel body and IP67 protection degree, specific for harsh industrial environments. High performance Intel processor and integrated weighing electronics Dini Argeo.

Working in cooperation with:

P.R.S. TORFBUD DAWID SZOPA
UL.KOPERNIKA 6 - 41500 - CHORZOW - POLAND
Tel. 0048-322413522 Fax. 0048-322413522
torfbud@wagielektroniczne.com.pl

**The best solution
for advanced industrial
applications**

TECHNICAL FEATURES

- Intel Celeron N3350 DualCore 64bit processor, 2Mb L2 cache, up to 2.4GHz.
- Intel HD Graphics 500 graphics processor.
- Pre-installed Windows 10 or Dini Argeo AFxxPC operating system.
- Resistive touch screen display, suitable for use with gloves and in the presence of water/condensation.
- Dimension 10.1", resolution 1280x800px, suitable for outside view (750 lumen).
- RAM 4GB DDR3L.
- Data storage SSD M.2 64GB.
- Integrated double 3W stereo speakers.
- Integrated RTC (for date/time, bios, etc.).
- Fanless technology, without cooling fans.
- AISI304 STAINLESS steel case with adjustable inclination.
- Standard ergonomic bracket, for bench use or wall mounting.
- Industrial communication ports with IP67 protection.
- IP67 STAINLESS steel valve to adjust humidity and pressure inside the case.
- IP67 overall protection degree.
- Working temperature: 0/60°C, 0/40°C for in legal-for-trade applications.
- Dimensions (l x h x w): 385x295x183.4 mm.
- Power supply 110/240Vac.

AVAILABLE INPUTS/OUTPUTS

- 2 USB 2.0 panel ports.
- 1 USB 3.0 internal port.
- 1 ETHERNET panel port, 10/100/1000 Mbps.
- 1 ETHERNET internal port, 10/100/1000 Mbps.
- 1 internal Display Port.
- 1 SATA III internal port (including cables).
- 1 RS485 internal port.
- 1 analogue input for scale.
- Integrated Alibi Memory, to carry out approved systems for legal-for-trade use.

STANDARD APPLICATIONS ON 6116PROAF

- AF01PC - Totalization
- AF02PC - Piece counter
- AF03PC - Weighbridge, first/second weighing
- AF04PC - Statistical checking
- AF05PC - Labelling

Main functions

- Up to 10,000 storages, according to the database.
- 2 list of storages exportable on flash drive or network folders.

ON REQUEST:

Reading, writing and sharing of archives on SQL databases.

SCALE INPUT

- Up to 10,000e or multirange 2 x 3000e @ 0,3 $\mu\text{V/d}$ in approved version CE-M.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Connectable with up to 8 analogue load cells with 350 Ohm input resistance.
- Certifications: EC Type Approval (EN45501) / OIML R76 / OIML R61 - MID / OIML R51
- Weight application reading from RS232 serial port.

DETAIL 1



DETAIL 2



Meticulously studied in every detail, for heavy industrial environments.



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418

P.R.S. TORFBUD DAWID SZOPA

UL.KOPERNIKA 6 - 41500 - CHORZOW - POLAND

Tel. 0048-322413522 Fax. 0048-322413522

torfbud@wagielektroniczne.com.pl

SALES AND TECHNICAL ASSISTANCE SERVICE