

# **JBQAI**

"JBQAI": EQUALISED JUNCTION BOX FOR ATEX ENVIRONMENTS, WITH UP TO 4 LOAD CELLS



Stainless steel junction box with IP66 protection from water and dust, and fitted with an intrinsically safe electronic board for junction and equalisation of load cells. Terminal boards with screws for easing th connection of the load cells and signal adjustment trimmer, for an accurate and reliable equalisation. Marking: ATEX II 2G Ex ib IIC T6 Gb for gases.

ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

The best solution for advanced industrial applications

## **TECHNICAL FEATURES**

- Designed and made according to the ATEX directive, group II category 2GD, according to the IEC/EN60079-0, IEC/EN60079-11, and IEC/EN60079-31 norms.
- Stainless steel case.
- PG9 metallic cable gland.
- Protection degree: IP66.
- Dimensions: 190x130x45mm (lxwxh).

NOTE: the dimensions are not compatibles for mounting on 4 load cells platforms/pallet weighers.

## ATEX PARAMETERS OF THE JUNCTION BOX

- Uo = Ui = 24Vdc
- Io = Ii = 174mA
- Co = Ci = 0mF
- Lo = Li = 0mH

or

- Uo = Ui = 12Vdc
- lo = li = 3,33A
- Co = Ci = 0mF
- Lo = Li = 0mH





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany **DINI ARGEO UK Ltd**United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd China **DINI ARGEO OCEANIA**Australia



### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

### SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 921784

- {	
- 1	
-	
- 1	
- 1	
- 1	
į	SALES AND TECHNICAL ASSISTANCE SERVICE