

LTFPRO

LTF "PROFESSIONAL" SERIES WEIGHING KIT FOR LIFT TRUCK FORKS



Pair of forks with an integrated weighing system, for lift trucks; easy to use, sturdy, and reliable. The indicator installable in the cabin eases the weighing operations, and can be fitted with a wide range of accessories. Functions through rechargeable battery or through direct powering from the lift truck. Compatible with any lift truck having a DIN 15173 - FEM fork holder plate, of the IIA or IIIA class (IIB optional). Available CE-M approved.

The best solution
for advanced industrial
applications

MAIN FEATURES

- Weight indicator in cabin with 17-key numerical/functional waterproof keypad, LCD backlit display with 6 high contrast 25-mm digits and easy to clean Waterproof IP65 ABS case resistant to harsh and corrosive environments. Integrated radio module, for communication with the weighing forks.
- Second weight indicator, attached to the forks, with 5-key numerical/functional waterproof keypad, LCD backlit display with 6 high contrast 25-mm digits protected in thick steel case. Integrated radio module, for communication with the indicator in cabin.
- Structure of the forks in painted steel with IP65 protection degree.
- Each fork weighs 75 kg (LTF25) and 90 kg (LTF50).
- Functions with 4 shear-beam IP68 load cells
- Accuracy: +/- 0.2% of the capacity
- Max. allowable overload: 200% of the nominal capacity.
- Max. horizontal inclination (flexibility): +/- 2° with the same precision features.
- Digital calibration and set-up through keyboard or PC with DINITOOLS.
- Forks power supply through rechargeable battery, 40-hour approximate operating time
- Indicator in cabin power supply through rechargeable battery (40-hour approximate operating time) or directly from the lift truck through optional power adapter.
- Programmable auto power saving function.
- Equipped with battery charger.

KEYBOARD FUNCTIONS AND PRINTOUT

- KEYBOARD: clearing, semi automatic tare, presettable tare, print and/or data transmission, selectable function command, on/off.
- PRINTOUT: customisable print layout.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Thermal printer option box.
- Time/Date.

SELECTABLE FUNCTIONS

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weighs totalisation
- Formulation
- +/- Check
- Percentage weighing
- Counting
- Hold and Peak

VERSIONS

Available versions				
Code	Plate	Max (kg)	d (kg)	CE-M 3000e (kg)
LTF1125AR-3	FEM2A	500 / 1000 / 2500	1 / 2 / 5	
LTF1125ARM-3	FEM2A	1000 / 2500		2 / 5
LTF1150AR-3	FEM3A	1000 / 2500 / 5000	2 / 5 / 10	
LTF1150ARM-3	FEM3A	2500 / 5000		5 / 10



www.diniargeo.com



DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Caltanissetta (RO) - Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE